
# LED - Wall Pack - 14" Full-Cut-Off Fixtures

### 70,000 HRS Life

### **The Next Generation of Lighting**





## LED

#### **Specification:**

- LED Driver Constant Curre t - Start Method InstantON - Hot Re-start InstantON - Universal Input Line Voltage 120-277 VAC - Input Line Frequency 50/60 Hz - System Life 70,000 Hrs. - Lumen Maintenance @50,000Hrs >85% - Color Temperature 5000°K - Color Rendering Index (CRI) >75 - 40°F - Minimum Operating Temperature - Maximum Ambient Temperature 125°F - Power Factor > 0.98 - Total Harmonic Distortion < 10% - Inrush Current Peak < 10 Amp Part 18, Subp. C - FCC Compliance

#### **Applications, Features, and Benefits**

- Cast aluminum housing powder coated
- Heat and impact resistant glass diffuser/lens
- -70,000 hrs LED driver made with long life components
- InstantON(TM) flicker-free Cold Start and Hot Re-Start
- High Power Factor, Low THD Driver
- Concealed continuous gasket seals against harmful dust, dirt, moisture and insects
- IP65 Rated for wet locations
- Up to 15 years Maintenance free operation
- Patented LED engine design with Advanced Thermal Management
- 5 Year Warranty

#### **Product Information**

ltem No.	Description	Watts	Initial Lumens	Line Voltage Supply	Line Current	Total Harmonic Distortion (THD)		Packaging Dimensions		
								Width	Length	Height
LED-21040FCT	LED - Wall Pack Full Cut Type	40	3,200	120-277 VAC	0.35-0.15 Amp	<10%	0.98	15.0 in. 381 mm	10.0 in. 254 mm	11.0 in. 280 mm
LED-21055FCT	LED - Wall Pack Full Cut Type	55	4,400	120-277 VAC	0.48-0.20 Amp	<10%	0.98	15.0 in. 381 mm	10.0 in. 254 mm	11.0 in. 280 mm
LED-21070FCT	LED - Wall Pack Full Cut Type	70	5,600	120-277 VAC	0.61-0.26 Amp	<10%	0.98	15.0 in. 381 mm	10.0 in. 254 mm	11.0 in. 280 mm

<sup>\*\*</sup> Optional Color Temperatures available: 3000°K, 4100°K

Fixture Weight = 20 lbs.

#### **Ordering Information**

(SAMPLE NUMBER: LED-21040FCT-UNV-LD-120V-BRZ)

Type Series Type 21 = Wall Pack FCT = Full Cut-Off

070 = 70W

Accessories
LD = Light Detector / Photocell

\* must verify operating voltage

Colors
BRZ = Dark Bronze
\* custom colors available

NEPTUN Light, Inc. Questions and Comments: service@neptunlight.com Toll-Free: 1-888-735-8330





